







The Matrix and Sonik range spotlights can be installed using the module S2 and bracket accessories 377 (refer to Fosnova Products).




acc. 375 upper cover	
14 white	145148
28 white	145149
35/49 white	145150
For direct light only applications.	




acc. 395 "S1" module	
14 m. silver	145080
14 white	145089
28 m. silver	145081
28 white	145090
35/49 m. silver.	145082
35/49 white	145091
Extruded aluminium with die-cast end caps.	




acc. 2515 suspension	
m. silver	993908
Suspension supplied with steel wire, 200 cm long with millimetric adjustment. Max load: 20 kg.	




acc. 2516 powered suspension	
m. silver	993910
Suspension supplied with steel wire, 100 cm long with millimetric adjustment and power cable. Max load 20 kg. Cm 200.	



acc. 397 simple cube	
m. silver	145092
white	145093
Made of die-cast aluminium and powder-coated. For "L", "T" o "X" jointing.	



acc. 398 cube for floodlights	
m. silver	145094
white	145095
Made of die-cast aluminium. For "L", "T" o "X" jointing and application of Fosnova spotlights.	



acc. 396 "S2" module	
14 m. silver	145086
14 white	145084
28 m. silver	145087
28 white	145078
35/49 m. silver.	145088
35/49 white	145079

To install Matrix and Sonik range spotlights with bracket access. 377 and module "S2" (refer to Fosnova Products).