




POWERLED

Azimuth IP65




(m)	Ø(m)	(lx)	max	med
0.180*4.0*4.0*	90.270*13.7*13.7	11866	23232	
1.0	0.146.0.131			
2.0	0.282.0.26	7367	5802	
3.0	0.423.0.39	3541	2582	
4.0	0.564.0.52	1992	1452	
5.0	0.705.0.65	1275	929	

Br	E1115/LBC	○
	E1115/LBI	○
	E1115/LBL	●
Ne	E1116/LBC	○
	E1116/LBI	○
	E1116/LBL	●
Gr	E1117/LBC	○
	E1117/LBI	○
	E1117/LBL	●

Alimentatore integrato Built-in control gear

12x2,5W 230V 700mA 10°

Submariner 175 IP68

(m)	Ø(m)	(lx)	max	med
0.180*1.0*1.0*	90.270*12.5*12.5	1992	649	
1.0	0.99.0.98			
2.0	0.99.0.98	273	162	
3.0	1.49.1.74	121	72	
4.0	1.98.2.32	68	41	
5.0	2.48.2.90	44	26	




Inox	E8242/LBC	○
	E8242/LBI	○
	E8242/LBL	●

Alimentatore IP67 remoto non in dotazione Remote IP67 control gear not supplied

644936/67

7x3W 230/24V 700mA 30°

Reef IP66




(m)	Ø(m)	(lx)	max	med
0.180*1.2*1.2*	90.270*13.7*13.7	2508	3589	
1.0	0.46.0.47			
2.0	0.92.0.94	1377	892	
3.0	1.31.1.41	612	399	
4.0	1.75.1.88	344	224	
5.0	2.18.2.35	220	144	

Ne	E1010/LBC	○
	E1010/LBI	○
	E1010/LBL	●
Gr	E1011/LBC	○
	E1011/LBI	○
	E1011/LBL	●

Alimentatore integrato Built-in control gear

15x1,2W 230V 350mA 30°

Li-Led IP65

(m)	Ø(m)	(lx)	max	med
0.180*1.2*1.2*	90.270*13.7*13.7	67	37	
1.0	0.82.0.80			
2.0	1.77.1.60	17	9	
3.0	2.56.2.40	7	4	
4.0	3.54.3.20	4	2	
5.0	4.43.3.01	3	1	





	E9053/P/LBC	○
	E9053/P/LBI	○
	E9053/P/LBL	●

Alimentatore remoto in dotazione Remote control gear supplied

1x3W 230V 350mA 45°/80°

POWERLED

Longlight Wall IP65

L=380 mm	12x1,2W 230V Gr	E8941/P/LBC	○
		E8941/P/LBI	○
		E8941/P/LBL	●
L=940 mm	36x1,2W 230V Gr	E8951/P/LBC	○
		E8951/P/LBI	○
		E8951/P/LBL	●
L=1240 mm	48x1,2W 230V Gr	E8957/P/LBC	○
		E8957/P/LBI	○
		E8957/P/LBL	●
L=1540 mm	60x1,2W 230V Gr	E8958/P/LBC	○
		E8958/P/LBI	○
		E8958/P/LBL	●

Alimentatore remoto in dotazione Remote control gear supplied

Longlight ST IP65









L1=345 mm	L2=395 mm	12x1,2W 230V Gr	E8941/PS/LBC	○
			E8941/PS/LBI	○
			E8941/PS/LBL	●
L1=906 mm	L2=956 mm	36x1,2W 230V Gr	E8951/PS/LBC	○
			E8951/PS/LBI	○
			E8951/PS/LBL	●
L1=1206 mm	L2=1246 mm	48x1,2W 230V Gr	E8957/PS/LBC	○
			E8957/PS/LBI	○
			E8957/PS/LBL	●
L1=1506 mm	L2=1546 mm	60x1,2W 230V Gr	E8958/PS/LBC	○
			E8958/PS/LBI	○
			E8958/PS/LBL	●

Alimentatore remoto in dotazione Remote control gear supplied




Mini Longlight ST IP65

L1=340 mm	L2=380 mm	12x1,2W 230V Als	E9052/P/LBC	○
			E9052/P/LBI	○
			E9052/P/LBL	●
L1=640 mm	L2=680 mm	24x1,2W 230V Als	E9062/P/LBC	○
			E9062/P/LBI	○
			E9062/P/LBL	●

Alimentatore remoto in dotazione Remote control gear supplied

New Activa IP65

L=606 mm	24x1,2W 230V Gr	E9020/LBC	○
		E9020/LBI	○
		E9020/LBL	●
L=906 mm	36x1,2W 230V Gr	E9021/LBC	○
		E9021/LBI	○
		E9021/LBL	●
L=1206 mm	48x1,2W 230V Gr	E9022/LBC	○
		E9022/LBI	○
		E9022/LBL	●
L=1506 mm	60x1,2W 230V Gr	E9023/LBC	○
		E9023/LBI	○
		E9023/LBL	●

Alimentatore integrato Built-in control gear

Legenda Legend

- Colore LED LED colour
- Colore apparecchio Fitting colour
- Br: Bianco White
- Ne: Nero Black
- Gr: Grigio Grey
- Al: Alluminio Aluminium
- LBI Bianco freddo Cool white
- LBC Bianco caldo Warm white
- LBL Blu Blue
- Apertura fascio Light beam
- Electronico Electronic
- Rotazione Rotation



www.sidespa.it



Side S.p.A.
Via C. Cattaneo, 90
20035 Lissone (MI)
Tel. +39 0392449001
Fax +39 0392459338
info@sidespa.it

Side Lighting LTD UK
Nr. S. Park str.
London SE19AB
Tel. 0044 2074036636
Fax 0044 2086874328
paulellis@side-lighting.co.uk

Side France
21/23 Rue Aristide Briand
94340 Joinville le Pont
Tel. 0033 1 42 83 42 29
Fax 0033 1 42 83 74 59
office@side-france.fr

Side Sud America
Pedro de Valdivia
nr. 5197 - Nuncio
Santiago - Chile
Tel. 0056 2238328
Fax 0056 27528304
www.spectrabl.cl
sideamerica@tie.cl

Side Japan
Azabu - z. bldg. 2f.,
2-6-10 Higashiazabu
Minato - ku
Tokio 106 - 0044 Japan
Tel. 0081 355494461
Fax 0081355494467
gio.crotti@sidejapan.com

POWER LED

Perchè scegliere POWER LED Why to choose POWER LED

- Lunga vita
Long life
- Risparmio energetico
Energy saving
- Elevato mantenimento del flusso luminoso nel tempo
High lasting time of the luminous flux
- Azzeramento degli interventi di manutenzione e cambio lampada
Zero costs for maintenance and lamp replacing
- Assenza totale di sfarfallamenti e nessun disturbo alla vista
Total lack of flickering and no eyes disturb
- Accensione immediata e massima efficienza luminosa istantanea
Immediate power-on and instantaneous luminous efficiency
- Elevata resistenza alle sollecitazioni meccaniche
High resistance to mechanical hits

Alogene/Halogens: 2000/3000h
 Alogenuri metallici/Metal halides: 6000/9000h
 Fluorescenti/Fluorescent: 8000/10000h
 Powerled: 40000/70000h

POWER LED


POWER LED




Azimuth




Submariner



Reef



Li-Led



Longlight Wall



Longlight ST



Mini Longlight ST



New Activa

