

Mini Doubleled tondo

Nuova gamma di applique esclusivamente a LED nella versione TONDA (design morbido con forme curve).





La tecnologia a LED ha permesso la miniaturizzazione di questi prodotti con il risultato di avere una altissima resa luminosa in piccole dimensioni.


New range of exclusively LED Applique in version ROUND (smooth curved).

Thanks to the LED technology they are miniaturized, with a very high luminous effect in small dimensions.




Mini Doubleled tondo



IP 65    

 H07RN-F
H07RN-F

- Corpo in alluminio pressofuso.
- Verniciatura in polveri con pre-trattamento speciale per esterni.
- Vetro di sicurezza temperato.
- Anello di finitura in acciaio inox AISI 316.
- Viteria in acciaio inox.
- Gruppo di alimentazione inserito nell'apparecchio.
- Ottiche in alluminio purissimo.
- Guarnizioni e pressacavo di tenuta in gomma siliconica.
- Flusso luminoso: 2 x 665 lm (led bianco).

- *Body and in die-cast aluminium.*
- *Powder coated with pretreatment for outdoor use.*
- *Tempered protection glass.*
- *AISI 316 steel finishing trim.*
- *Inox steel screws.*
- *Control gear in the body.*
- *Very pure aluminium optics.*
- *Silicon rubber gaskets and cable gland.*
- *Luminous flux: 2 x 665 lm (white led).*



Br	E4900/LBC					
Ne	E4901/LBC	2x13W	230V		40°	
Gr	E4902/LBC		700mA			
Br	E4900/LBI					
Ne	E4901/LBI	2x13W	230V		40°	
Gr	E4902/LBI		700mA			

A richiesta versione con 1 o 2 lame di luce / On request 1 or 2 blade light version