

Olodum micro cover AL



Olodum micro cover AL

IK 07
IP 67



H05RN-F
H05RN-F


Carico statico 2000 kg
Static load 2000 kg

Velocità max carrabilità 5 km/h
Drive-over max speed 5 km/h

- Corpo Inox aisi 316L.
- Calotta in alluminio pressofuso.
- Doppia verniciatura in polveri poliestere.
- Diffusore in policarbonato anti-UV.
- Cassaforma di contenimento in PA (da ordinare a parte).
- Pressacavo in ottone nichelato PG7 (diametro cavi utilizzabili 5 ÷ 7mm).
- Viti in acciaio INOX.
- Alimentatore remoto non in dotazione.




- *Inox aisi 316L.*
- *Die-cast aluminium cover.*
- *Double powder coated painting.*
- *Anti-UV polycarbonate diffuser.*
- *Housing made of PA (not included).*
- *PG7 nichel brass cable gland (use cables with diameter 5÷7 mm).*
- *Inox steel screws*
- *Remote ballast not included*




Versione radiale con powered / Powered radial version

Gr ○ **E8399/LBI** 1x1,2W 350mA
Gr ● **E8399/LBL**




Versione mono emissione con powered / Powered mono emission version

Gr ○ **E8399/3/LBI** 1x1,2W 350mA
Gr ● **E8399/3/LBL**



OP.  .../TSC TORX Viti di sicurezza / Safety screws

ACC.



185 Cassaforma per incasso
Housing for recessed lights

Trasformatori: vedi sezione ALIMENTATORI / Transformers: see POWER SUPPLIES section